

Updated: April 2021

Flo	oor ele	anin	g			
Item no.	Product	Size	Packaging	Kolli size	Pallet size	Ecolabel- led
	UN SÆBE combined cleaning and or ardwood floors.	care product for all floors	which tolerate w	rater. Is especia	ally suitable for s	stone, tiles a
41010	Brill. fl. brun sæbe	5L	Can	3	108	
41012	Brill. fl. brun sæbe	200L	Drum	1	2	
shrink-proof	Floor 930 2. 337 is used in carpet cleaning ma and colorfast before use.) Floor Ca irt, the carpet can be wetted with F	orp. 337 quickly and effect	ctively loosens dir	t and fat from	the carpet fiber	
26039	Floor Carp. 337	5L	Can	3	108	dillo.
) JL	Carr			-
that the floo) has a great cleaning and caring ef irs are periodically washed with Un among others is resistant to black r	fect. FLOOR F 930 is well i Surface 920 in order to	suited for all floo avoid too much s	oap film. FLOC	OR F 930 leaves	commende
that the floo layer which a	rs are periodically washed with Un	fect. FLOOR F 930 is well i Surface 920 in order to	suited for all floo avoid too much s	oap film. FLOC	OR F 930 leaves a	commende
that the floo layer which a 26286 FLOOR POLIS	rs are periodically washed with Un among others is resistant to black r	fect. FLOOR F 930 is well i Surface 920 in order to marks and salt corrosion. 5L ing of all floor types. Floor	suited for all floo avoid too much s Scratched surface Can or Polish 336 is ba	oap film. FLOC es are can be r 3 ased on polym	OR F 930 leaves a repaired. 108 er wax und leave	ecommended a strong cari
that the floo layer which a 26286 FLOOR POLIS ling, silk mat	rs are periodically washed with Un among others is resistant to black r Floor F 930 SH 336 is well suited for daily clean	fect. FLOOR F 930 is well i Surface 920 in order to marks and salt corrosion. 5L ing of all floor types. Floor	suited for all floo avoid too much s Scratched surface Can or Polish 336 is ba	oap film. FLOC es are can be r 3 ased on polym	OR F 930 leaves a repaired. 108 er wax und leave	ecommended a strong cari
that the floo layer which a 26286 FLOOR POLIS ling, silk mat 41660 FLOOR RESIN	rs are periodically washed with Un among others is resistant to black r Floor F 930 SH 336 is well suited for daily clean and anti-slip surface. It is recomm	fect. FLOOR F 930 is well i Surface 920 in order to marks and salt corrosion. 5L ing of all floor types. Floe ended that the floors are 5L emoval of resin on sports	suited for all floo avoid too much s Scratched surface Can or Polish 336 is bate periodically was Can	oap film. FLOC es are can be r 3 ased on polym hed with an U 3 esin 338 can be	DR F 930 leaves a repaired. 108 er wax und leaveni Surface 720. 108 e used both mar	ecommended a strong cari es a dirtrepe
that the floo layer which a 26286 FLOOR POLIS ling, silk mat 41660 FLOOR RESIN in a floor wa	rs are periodically washed with Unamong others is resistant to black r Floor F 930 SH 336 is well suited for daily clean and anti-slip surface. It is recomm Floor Polish 336	fect. FLOOR F 930 is well i Surface 920 in order to marks and salt corrosion. 5L ing of all floor types. Floe ended that the floors are 5L emoval of resin on sports	suited for all floo avoid too much s Scratched surface Can or Polish 336 is bate periodically was Can	oap film. FLOC es are can be r 3 ased on polym hed with an U 3 esin 338 can be	DR F 930 leaves a repaired. 108 er wax und leaveni Surface 720. 108 e used both mar	ecommended a strong cari es a dirtrepe
that the floo layer which a 26286 FLOOR POLIS ling, silk mat 41660 FLOOR RESIN in a floor wa 41046 FLOOR TERR has an espec	rs are periodically washed with Unamong others is resistant to black r Floor F 930 SH 336 is well suited for daily clean and anti-slip surface. It is recomm Floor Polish 336 N 338 is especially well suited for resisher. Floor Resin 338 can be used on	fect. FLOOR F 930 is well i Surface 920 in order to marks and salt corrosion. 5L ing of all floor types. Floorended that the floors are 5L emoval of resin on sports on all types of floors. Use 5L ind caring effect. Floor Tecles I linoleum and rubber floors.	suited for all floo avoid too much s Scratched surface Can or Polish 336 is be e periodically was Can flooring. Floor Re d with caution or Can errazzo W 330 is woring. Floor Terra	oap film. FLOC es are can be r 3 ased on polym hed with an U 3 esin 338 can be i linoleum and 3 vell suited for a zzo W 330 leav	PR F 930 leaves a repaired. 108 er wax und leaven Surface 720. 108 e used both mar PU floors. 108 all floors, but the ves a strong cari	es a dirtrepe
that the floo layer which a 26286 FLOOR POLIS ling, silk mat 41660 FLOOR RESIN in a floor wa 41046 FLOOR TERR has an espec which is resi	rs are periodically washed with Unamong others is resistant to black refloor F 930 SH 336 is well suited for daily clean and anti-slip surface. It is recomm Floor Polish 336 N 338 is especially well suited for resher. Floor Resin 338 can be used of Floor Resin 338 AZZO W 330 has a great cleaning a cially great effect on vinyl, terrazzo,	fect. FLOOR F 930 is well i Surface 920 in order to marks and salt corrosion. 5L ing of all floor types. Floorended that the floors are 5L emoval of resin on sports on all types of floors. Use 5L ind caring effect. Floor Tecles I linoleum and rubber floors.	suited for all floo avoid too much s Scratched surface Can or Polish 336 is be e periodically was Can flooring. Floor Re d with caution or Can errazzo W 330 is woring. Floor Terra	oap film. FLOC es are can be r 3 ased on polym hed with an U 3 esin 338 can be i linoleum and 3 vell suited for a zzo W 330 leav	PR F 930 leaves a repaired. 108 er wax und leaven Surface 720. 108 e used both mar PU floors. 108 all floors, but the ves a strong cari	es a dirtrepe
that the floo layer which a 26286 FLOOR POLIS ling, silk mat 41660 FLOOR RESIN in a floor wa 41046 FLOOR TERR has an espec which is resis 22073 FLOOR TILE 3	Floor F 930 SH 336 is well suited for daily clean and anti-slip surface. It is recomm Floor Polish 336 N 338 is especially well suited for resher. Floor Resin 338 can be used of Floor Resin 338 AZZO W 330 has a great cleaning a cially great effect on vinyl, terrazzo, stant to black marks, salt corrosion	fect. FLOOR F 930 is well i Surface 920 in order to marks and salt corrosion. 5L ing of all floor types. Florended that the floors are 5L emoval of resin on sports on all types of floors. Use 5L ind caring effect. Floor Tellinoleum and rubber floor and more. Floor Terrazz 5L ing agent for all floor types.	suited for all floo avoid too much s Scratched surface Can or Polish 336 is bate periodically was Can flooring. Floor Red with caution or Can errazzo W 330 is woring. Floor Terrato W 330 can repa Can es which tolerate	oap film. FLOC es are can be r 3 ased on polym hed with an U 3 esin 338 can be a linoleum and 3 vell suited for a zzo W 330 leav ir scratched su	PR F 930 leaves a repaired. 108 er wax und leaven Surface 720. 108 e used both mar PU floors. 108 all floors, but the ves a strong cari arfaces. 108 here a caring effective a strong effective a caring effective a strong effective a strong effective a caring effective a strong effective a caring effective a strong effective a caring effective a strong effective a s	es a dirtrepe
that the floo layer which a 26286 FLOOR POLIS ling, silk mat 41660 FLOOR RESIN in a floor wa 41046 FLOOR TERR has an espec which is resis 22073 FLOOR TILE 3	rs are periodically washed with Unamong others is resistant to black refloor F 930 SH 336 is well suited for daily clean and anti-slip surface. It is recomm Floor Polish 336 N 338 is especially well suited for resher. Floor Resin 338 can be used of Floor Resin 338 AZZO W 330 has a great cleaning a cially great effect on vinyl, terrazzo, stant to black marks, salt corrosion Floor Terrazzo W 330 S32 is a combined cleaning and car	fect. FLOOR F 930 is well i Surface 920 in order to marks and salt corrosion. 5L ing of all floor types. Florended that the floors are 5L emoval of resin on sports on all types of floors. Use 5L ind caring effect. Floor Tellinoleum and rubber floor and more. Floor Terrazz 5L ing agent for all floor types.	suited for all floo avoid too much s Scratched surface Can or Polish 336 is bate periodically was Can flooring. Floor Red with caution or Can errazzo W 330 is woring. Floor Terrato W 330 can repa Can es which tolerate	oap film. FLOC es are can be r 3 ased on polym hed with an U 3 esin 338 can be a linoleum and 3 vell suited for a zzo W 330 leav ir scratched su	PR F 930 leaves a repaired. 108 er wax und leaven Surface 720. 108 e used both mar PU floors. 108 all floors, but the ves a strong cari arfaces. 108 here a caring effective a strong effective a caring effective a strong effective a strong effective a caring effective a strong effective a caring effective a strong effective a caring effective a strong effective a s	es a dirtrepe







...Floor cleaning, continued 1

Item no.	Product	Size	Packaging	Kolli size	Pallet size	Ecolabel- led			
FOAM ACID 335 is a strongly acidic foam cleaning agent for use in the tobacco and alcohol industry as well as in the food industry. Use on acid-resistant surfaces where a quick and effective cleaning and descaling in for example industrial kitchens, the food industry shower rooms, public swimming pools and more is required. Foam Acid 335 is well suited for use on vertical surfaces because the foaming cleaning agent makes stable foam with very good adhesion. After 5-15 minutes, the foam is rinsed off with clean water. Do not use Foam Acid 335 on untreated aluminum.									
22148	Foam Acid 335	5L	Can	3	108				
	24 is a strong foam alganing agent. Use on all	alina rasistant							
For example of	34 is a strong foam cleaning agent. Use on alk on tiles, concrete, stainless steel and more. Foa akes stable foam with very good adhesion. Do	am Alka 334 is v	vell suited for u	ise on vertical s	surfaces as the				
For example on the same of the	on tiles, concrete, stainless steel and more. For	am Alka 334 is v	vell suited for u	ise on vertical s	surfaces as the				
For example on the following agent made agent made at 1803 FOAM NEUTR	on tiles, concrete, stainless steel and more. For akes stable foam with very good adhesion. Do	am Alka 334 is word use Foam A 5L ning of shower i	vell suited for u Alka 334 on unt Can rooms, wet roo	reated aluminu 3 ms, industrial k	surfaces as the tim. 108 itchens and mo	foaming clea			

Innovators in Cleaning